

LISTING OF CLAIMS

1 through 42. (cancelled)

43. (previously presented) An objective constructed of a single glass material for use with light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range, comprising:

at least one focusing lens having diameter less than approximately 100 millimeters receiving said light energy and transmitting focused light energy;

at least one field lens having diameter less than approximately 100 millimeters, receiving said focused light energy and transmitting intermediate light energy; and

at least one Mangin mirror element having diameter less than 100 millimeters receiving said intermediate light energy and providing controlled light energy through an immersion substance to a specimen.

44. (previously presented) The objective of claim 43, wherein said objective has a field size of approximately 0.15mm.

45. (previously presented) The objective of claim 43, configured to have a numerical aperture of approximately 1.2.

46. (previously presented) The objective of claim 43, wherein each lens used in the objective has a diameter of less than approximately 25 millimeters.

47. (previously presented) The objective of claim 43, said objective used with a microscope having a flange, wherein the flange may be located at least approximately 45 millimeters from the specimen during normal operation.

48. (previously presented) The objective of claim 47, wherein the flange may be located at least approximately 100 millimeters from the specimen during normal operation.

49. (previously presented) The objective of claim 43, wherein only two glass materials are used.

50. (previously presented) The objective of claim 43, wherein the immersion substance is water.

51. (previously presented) The objective of claim 43, wherein the immersion substance is oil.

52. (previously presented) The objective of claim 43, wherein the immersion substance is silicone gel.

53. (previously presented) The objective of claim 43, wherein the objective is optimized to produce minimum spherical aberration, axial color, and chromatic variation of aberrations.

54. (previously presented) The objective of claim 43, wherein the at least one mangin mirror element is optimized to produce spherical, axial color, and chromatic variation of aberrations to compensate for aberrations induced by the focusing lens group.

55. (previously presented) An objective constructed of a single glass material for use with light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range, comprising:

at least one focusing lens having diameter less than approximately 100 millimeters receiving said light energy and transmitting focused light energy;

at least one field lens having diameter less than approximately 100 millimeters, receiving said focused light energy and transmitting intermediate light energy; and

at least one Mangin mirror element having diameter less than 100 millimeters receiving said intermediate light energy and providing controlled light energy through an immersion substance to a specimen.

56. (previously presented) The objective of claim 55, wherein said objective has a field size of approximately 0.15mm.

57. (previously presented) The objective of claim 55, wherein said at least one Mangin mirror element comprises:

a single lens/mirror element comprising:

a substantially curved concave surface; and

a second minimally curved surface;

wherein both surfaces of the single lens/mirror element are reflective with small central apertures through which light energy may pass.

58. (previously presented) The objective of claim 55, said objective having a numerical aperture of greater than approximately 1.0 at the specimen.

59. (previously presented) The objective of claim 55, wherein each lens in the objective has a diameter of less than approximately 25 millimeters.

60. (previously presented) The objective of claim 55, said objective having an ability to be employed with a microscope having a flange, wherein the flange may be located less than no more than approximately 45 millimeters from the specimen during normal operation.

61. (previously presented) The objective of claim 55, said objective employing no more than two glass materials.

62. (previously presented) The objective of claim 61, wherein the no more than two glass materials comprise fused silica and calcium fluoride.

63. (previously presented) The objective of claim 55, wherein the immersion substance comprises one from a group comprising water, oil, and silicone gel.

64. (previously presented) The objective of claim 55, configured to have a numerical aperture of approximately 1.2.

65. (previously presented) A method for inspecting a specimen, comprising:

providing light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range;

focusing said light energy using at least one lens into focused light energy, where each lens used in said focusing has diameter less than approximately 100 millimeters;

receiving said focused light energy and converting said focused light energy into intermediate light energy; and

receiving said intermediate light energy and providing controlled light energy through an immersion substance to a specimen.

66. (previously presented) The method of claim 65, wherein said method results in a field size of approximately 0.15mm.

Please add the following new claims:

67. (new) The method of claim 66, wherein said providing, focusing, focused light energy receiving, and intermediate light energy receiving results in a field size of approximately 0.15mm.

68. (new) The method of claim 66, providing, focusing, focused light energy receiving, and intermediate light energy receiving results in a numerical aperture of approximately 1.2.

69. (new) The method of claim 66, wherein each lens used has a diameter of less than approximately 25 millimeters.

70. (new) The method of claim 66, said method employed with a microscope having a flange, wherein the flange may be located at least approximately 45 millimeters from the specimen during normal operation.

71. (new) The method of claim 70, wherein the flange may be located at least approximately 100 millimeters from the specimen during normal operation.

72. (new) The method of claim 66, wherein only two glass materials are used for lenses.

73. (new) The method of claim 66, wherein the immersion substance is water.

74. (new) The method of claim 66, wherein the immersion substance is oil.

75. (new) The method of claim 66, wherein the immersion substance is silicone gel.

76. (new) The method of claim 66, wherein providing, focusing, focused light energy receiving, and intermediate light energy receiving is optimized to produce minimum spherical aberration, axial color, and chromatic variation of aberrations.

77. (new) The method of claim 66, wherein the providing, focusing, focused light energy receiving, and intermediate light energy receiving is optimized to produce spherical, axial color, and chromatic variation of aberrations to compensate for aberrations induced.

78. (new) An objective for use with light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range, comprising:

at least one focusing lens receiving said light energy and transmitting focused light energy;

at least one field lens receiving said focused light energy and transmitting intermediate light energy; and

at least one Mangin mirror element having diameter less than 100 millimeters receiving said intermediate light energy and providing controlled light energy through an immersion substance to a specimen.

79. (new) The objective of claim 78, wherein said objective has a field size of approximately 0.15mm.

80. (new) The objective of claim 78, configured to have a numerical aperture of approximately 1.2.

81. (new) The objective of claim 78, wherein each lens used in the objective has a diameter of less than approximately 25 millimeters.

82. (new) The objective of claim 78, said objective used with a microscope having a flange, wherein the flange may be located at least approximately 45 millimeters from the specimen during normal operation.

83. (new) The objective of claim 82, wherein the flange may be located at least approximately 100 millimeters from the specimen during normal operation.

84. (new) The objective of claim 78, wherein only two glass materials are used.

85. (new) The objective of claim 78, wherein the immersion substance is water.

86. (new) The objective of claim 78, wherein the immersion substance is oil.

87. (new) The objective of claim 78, wherein the immersion substance is silicone gel.

88. (new) The objective of claim 78, wherein the objective is optimized to produce minimum spherical aberration, axial color, and chromatic variation of aberrations.

89. (new) The objective of claim 78, wherein the at least one mangin mirror element is optimized to produce spherical, axial color, and chromatic variation of aberrations to compensate for aberrations induced by the focusing lens group.

90. (new) An objective for use with light energy having a wavelength in the range of approximately 157 nanometers through the infrared light range, comprising:

at least one focusing lens receiving said light energy and transmitting focused light energy;

at least one field lens receiving said focused light energy and transmitting intermediate light energy; and

at least one Mangin mirror element having diameter less than 100 millimeters receiving said intermediate light energy and providing controlled light energy through an immersion substance to a specimen.

91. (new) The objective of claim 90, wherein said objective has a field size of approximately 0.15mm.

92. (new) The objective of claim 90, wherein said at least one Mangin mirror element comprises:

a single lens/mirror element comprising:

a substantially curved concave surface; and

a second minimally curved surface;

wherein both surfaces of the single lens/mirror element are reflective with small central apertures through which light energy may pass.

93. (new) The objective of claim 90, said objective having a numerical aperture of greater than approximately 1.0 at the specimen.

94. (new) The objective of claim 90, wherein each lens in the objective has a diameter of less than approximately 25 millimeters.

95. (new) The objective of claim 90, said objective having an ability to be employed with a microscope having a flange, wherein the flange may be located less than no more than approximately 45 millimeters from the specimen during normal operation.

96. (new) The objective of claim 90, said objective employing no more than two glass materials.

97. (new) The objective of claim 96, wherein the no more than two glass materials comprise fused silica and calcium fluoride.

98. (new) The objective of claim 90, wherein the immersion substance comprises one from a group comprising water, oil, and silicone gel.

99. (new) The objective of claim 90, configured to have a numerical aperture of approximately 1.2.